

PRODUCT DESCRIPTION

Back to Black is a high-performance water-based colour reviver and sealer which restores and enhances the appearance of faded black and dark coloured natural stone. Back to Black is especially suited for use on oxidised black and dark limestones, black slate, black granite and concrete paving.

This is a highly effective impregnating formula which provides an advanced breathable protection and superior stain resistance. The treated surface remains permeable to air and water vapour giving long lasting protection. Back to Black dries with a matt finish to give an attractive intensified look.

This sealer is an environmentally friendly product, completely waterborne, non-toxic, solvent and silicone free.

BENEFITS

- Delays the penetration of water and oily liquids allowing time to clean up any spillage to prevent staining
- UV resistant
- Non-flammable
- Non-toxic
- Environmentally friendly
- Non hazardous

APPLICATION

Not suitable if surfaces have been treated previously with a silicone or stearate-based water repellent.

Always test a small inconspicuous area before proceeding to ensure the finished result is satisfactory and to identify the optimum colour you wish to achieve.

Shake the container well before use.

Do not dilute or mix with other products.

Ensure the surface to be treated is clean, dust-free and dry before application.

Apply with either a low-pressure pump sprayer or brush.

Work in small areas when applying Back to Black as multiple coats may be required depending on how porous your product is and the colour you wish to achieve.

Back to Black is water based and the product must be applied until saturation is achieved to ensure 100% product efficiency. You must not let the Back to Black dry between coats, each extra coat needs to be reapplied before the previous coat dries, wet on wet.

Product will normally be touch dry within 1-6 hours, allowing longer in cold conditions. Optimum performance is reached after 5 to 7 days.

PACKAGING

5 litre (169floz) container

COVERAGE

1 Litre = 5m² to 16m² (33.8floz = 54ft² to 172ft²)

The figures indicated are approximate and should only be used as a general guideline.

STORAGE

Use within 24 months from the date of manufacture. Store in the original unopened container in a clean, dry area and ideally at 5°C - 25°C (41°F - 77°F).

CLEANING EQUIPMENT

Clean tools and equipment immediately after use with water.

RECOMMENDATIONS

Do not apply during wet weather, frost or if rain is forecast. Ideal application temperature to obtain the best results is <5°C and >25°C (<41°F and >77°F). Please be aware darker coloured paving will have a considerably higher surface temperature in warmer weather conditions.

Do not use on any metallic surfaces.

This product is not designed for non-absorbent surfaces.

HEALTH AND SAFETY

KEEP OUT OF THE REACH OF CHILDREN.

Hand Protection Wear domestic gloves.

Skin Protection Wear protective clothing.

Respiratory Protection Under normal conditions of use where there is adequate ventilation, no special respiratory protection equipment is needed.

Eye Protection If there is a real risk of splashing, wear protective goggles.

In case of ingestion Do not provoke vomiting. Contact a doctor or a specialist.

Please dispose of packaging and waste products in line with current environmental legislation.



Disclaimer: Pavetuf Back to Black, if used in accordance with the instructions provided, should produce results as described. Talasey Ltd does not offer nor imply any guarantees. No liability will be accepted from either the supplier nor the manufacturer, for changes in appearance or markings of the material on which it is used. Revised BTBPL0120V1



5060582651156



Distributed worldwide by Talasey Ltd
www.talasey.co.uk

Before use, please read the safety data sheet available on
www.pavetuf.com

For further information or technical advice call

☎ 0330 333 8030 or ☎ (888) 240 8704