

DECLARATION OF PERFORMANCE

Harvest Classicstone, Calibrated Flagstone Project Pack

1. Product Type: Quartzitic Sandstone

2 Unique Identification Code(s): NPPHVFCA60-18-PP

3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Commercial And Domestic Paving For External Use

4. Manufacturer: Natural Paving Products (UK) Ltd (Stone Exporters (India) Pvt Ltd.)
Kera
India

5. Authorised Representative: Steve Milburn

6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR: Level 4

7. Harmonised Standard: EN1341:2012

8. Notified Body: N/A

9. Declared Performance

| Essential Characteristic | Performance | Harmonised Technical Specification EN1341:2012 |
|--|-------------|---|
| Release Of Dangerous Substances | NPD | 4.11 |
| Flexural Strength - Lowest Expected Value | 14.6MPa | EN12372 4.4 |
| Slip Resistance Wet Value | 56 | EN14231 4.6.1 |
| Slip Resistance Dry Value | 62 | EN14231 4.6.1 |
| Skid Resistance | NPD | 4.6.2 |
| Freeze/Thaw Resistance – Mean values before and after freeze/thaw test | 33/28.8MPa | EN12371 4.3.1 |
| Freeze/Thaw Resistance – De-icing salts | NPD | 4.3.2 |
| Polishing In Use | NPD | 4.6.3 |
| Water Absorption | 2.6% | EN13755 |
| Abrasion Resistance | 14.5mm | EN14157 |

- 10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function: Mark Wall, Managing Director

Place and date of issue:

Belton Road
Sandtoft
Doncaster
North Lincolnshire
DN8 5SX

Signature:

A handwritten signature in black ink, appearing to read 'M. Wall', is written over a light grey rectangular background.

27th April 2016